



- SPECIFICATION:**
1. CURRENT RATING: 2A 50V AC/DC.
 2. CONTACT RESISTANCE: 60m MAX AT DC 20mA.
 3. INSULATION RESISTANCE: 100M MIN AT 500V DC.
 4. OPERATING TEMPERATURE RANGE: -25°C TO +85°C.
 5. MARKED " " ARE IMPORTANT DIMENSIONS.

Bill Of Materials:

| No. | TITLE | PART NO. | MATERIAL | FINISH (OR COLOR) | NO. |
|-----|--------------|-----------------|---------------------------|-------------------|-----|
| 1 | HOUSING | 118-08-3-H-1-BK | LCP+30%GF, UL94 V-0 | BLACK | 1 |
| 2 | TERMINAL | 118-08-3-T-1-XX | BeCu, T=0.15mm | GLD PLATED | 3 |
| 3 | GROUND SLICE | 118-08-3-G-1-0T | BRASS(C2680R-H), T=0.20mm | TIN PLATED | 2 |
| 4 | GO TO SLICE | 118-08-3-G-2-0T | BRASS(C2680R-H), T=0.20mm | TIN PLATED | 2 |

UNITS: mm

GENERAL TOLERANCE

| | |
|-------------|--------------|
| X. ± 5° | 0. XX ± 0.3 |
| X. 1 ± 2° | 0. XX ± 0.2 |
| XX. ± 1° | 0. XXX ± 0.1 |
| XXX. ± 0.5° | |

CSCONN

PART NO. (INTENDED USE)
CBA-250412-65

TITLE: BATTERY 4P 2.5MM H=6.5MM

DWG NO. BATTERY

APPD: SKI1A

CHKD: SKI1A

DR: Kitty

CSCONN PRECISE ELECTRONICS CO., LTD

SCALE: 1:1

SHEET: 1 OF 1

REV: A