



RECOMMENDED PC BOARD LAYOUT
TOLERANCE: ±0.05[TOP VIEW]

NOTES

1. MATERIAL & FLASH/PLATED

1.1 HOUSING: HIGH TEMP. THERMOPLASTIC+GLASS FIBRE

.JUL 94V-0; COLOR: BLACK

1.2 TERMINAL: COPPER ALLOY

PLATED: 15μ" GOLD ON CONTACT AREA, 1.5μ" GOLD ON

SOLDER AREA, GOLD FLASH ALL OVER.

BASE NICKEL: 50~100μ"

1.3 COVER: HIGH TEMP. THERMOPLASTIC+GLASS FIBRE

.JUL 94V-0; COLOR: BLACK

2. PACKAGE: TAPE/REEL

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE:	
X. ° ±5°	0. X ±0.3	CBA30032101001		BATTERY 3P 3.0MM H=2.1MM	
X. 1 ±2°	0. XX ±0.2	APPD:		DWG. NO.	
XX. ±1°	0. XXX ±0.1	CHKD: Skila		BATTERY	
XXX. ±0.5°		DR: Kitty		SCALE SHEET REV	
				1:1 1 OF 1 A	