



Contact No.	Assignment
PIN1/C1	VCC (Supply voltage)
PIN2/C2	RST (Reset signal)
PIN3/C3	CLK (Clock signal)
PIN5/C5	GND (Ground)
PIN6/C6	VPP Variable supply voltage (e.g. programming voltage)
PIN7/C7	I/O (Data input/output)

PCB AREA  
 CONNECT AREA  
 KEEP OUT AREA  
 PCB穿孔

- MATERIALS**
- HOUSING: THERMOPLASTIC (UL 94V-0).
  - TERMINAL: COPPER ALLOY, PLATING: AND SOLDER TAILS, NICKEL PLATED OVERALL.
  - SHELL: SUS
- PLATING: NICKEL PLATED OVERALL.  
GOLD PLATED ON SOLDER TAILS

- SPECIFICATIONS:**
- CURRENT RATING: 0.5AMP MAX.
  - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
  - CONTACT RESISTANCE: 40M OHMS MAX.
  - INSULATION RESISTANCE: 1000M OHMS MIN AT 250V DC.
  - OPERATION TEMPERATURE: -25° C ~ +85° C.
  - OPERATING VOLTAGE: 250V (AC/DC).

<b>UNITS: mm</b>		<b>CSCONN</b>		<b>CSCONN PRECISE ELECTRONICS CO.,LTD</b>	
<b>GENERAL TOLERANCE</b>		<b>PART NO.(INTENDED USE)</b>		<b>TITLE:</b>	
X. ±5°	0.X±0.25	CSI0614415001		MICRO SIM CARD 6P 1.5H	
X. ±2°	0.XX±0.2	<b>APPD:</b>		<b>DWG NO.</b>	
X. ±1°	0.XXX±0.1	SK11a		SIM CARD	
<b>CHKD:</b>		<b>DR:</b>		<b>SCALE</b>	
SK11a		Kitty		1:1	
				<b>SHEET</b>	
				1 OF 1	
				<b>REV</b>	
				A	