



Electrical:

Current Rating : 0.5mA AC/DC max.
 Voltage Rating : 125V AC/DC
 Ambient Temperature Range : -25° C~+85° C
 Storage Temperature Range : -25° C~+85° C
 Ambient Humidity Range : 95% R.H. Max.
 Contact Resistance:100m max.
 Insulation Resistance:1000M min./500VDC
 Mating Cycles:5,000 Insertions
 产品耐插温度: 260° C

| PIN NO. | PIN ASSIGNMENT |
|---------|----------------|
| 1# | DM12 |
| 2# | CD/INT3 |
| 3# | CD |
| 4# | VDD |
| 5# | CLK |
| 6# | VSS |
| 7# | DATA |
| 8# | DM11 |

| UNITS: | mm |
|-------------------|------------|
| GENERAL TOLERANCE | |
| X. ±5° | 0. X±0.25 |
| X. 1±2° | 0. XX±0.2 |
| XX. ±1° | 0. XXX±0.1 |

CSCONN
 CS CONN PRECISE ELECTRONICS CO.,LTD

PART NO.(INTENDED USE)
 CTF1410168001

TITLE:
 T-FLASH CARD PUSH H=1.68MM

DWG NO. TFP CARD

APPD:
 CHKD: SK11a
 DR: Kitty

SCALE 1:1
 SHEET 1 OF 1
 REV A

A B C D E

1 2 3 4 5 6 7 8